



Flexiclean LC-200

Overview

- Leather Cleaner Concentrate
- Safe for Use on Leather
- Leaves Leather Soft, Supple and Ready to Protect
- Restores Like-New Appearance to Leather
- Removes Built Up Grime, Dirt, and Oils
- Removes Stains from Leather
- Easy to Fragrance: Readily Accepts Fragrance
- Easy to Use: Spray, Wipe or Foam on And Wipe Off

Applications

- Mild and Heavy Duty Cleaners for Leather
- Leather Cleaner Wipes
- Foamable and Moussable Leather Cleaners

Technical Information

Flexiclean LC-200 is a proven, safe leather cleaner concentrate that is easily and readily fragranced. Add the fragrance to the LC-200 and mix until homogeneous and then dilute in water and the LC-200 will carry the fragrance oil into the water (add dye and preservative as needed). This product is mild enough to use on the

most sensitive leathers as long as the leather, dyes and finish are water fast. Once the leather is cleaned, it is ready to be protected with Flexipel LPC-306 (oil and water repellent) or if the leather is old, cracked or scratched, it can be conditioned before protection with Flexicon LC-65.

FORMULARY

<u>Mild Cleaner</u>	
Water	85%
Flexiclean LC-200	15%

<u>Heavy Duty Cleaner</u>	
Water	75%
Flexiclean LC-200	25%

- Add LC-200 to water and mix until uniform. Add preservative, fragrance and dye as desired. If adding a fragrance oil, it is recommended that it be predissolved in the LC-200 which will carry the fragrance into the water. Adjust LC-200 use level based on cost/performance properties desired. Thick and creamy formulations can be supplied on request if desired.
- Wipe, spray or foam on and wipe off with soft cloth.

Unfinished leathers may be slightly darkened. Always test the product in an inconspicuous area to make sure treated appearance is acceptable. Unfinished leathers, Nubucks and Suedes are best cleaned using foam from the cleaner to minimize water wetting of the leather. Foams can be generated by applying the cleaner to a sponge and rapidly squeezing the sponge to generate foam or by using a foaming sprayer or a mousing applicator head. The idea is to minimize darkening of these unfinished leathers by not allowing the water to soak into the surface.

Note: Be sure to review ICT's Flexicon LC-65 (leather cleaner and conditioner), Flexipel AM-98 (a dilutable oil/water repellent for Nubucks and Suedes), Flexipel AM-99 (a dilutable oil/water repellent for finished leather), and Flexipel LPC-306 (a ready to use, rich leather protection cream).

Typical Properties

Appearance	Clear, Colorless to Pale Yellow Liquid
Density @ 25°C	1.0 g/ml (8.3 lbs/gal)
pH (as is)	7.0 - 10.0
Water Solubility	Soluble
Boiling Point	Approx. 100°C

Packaging and Handling

Flexiclean LC-200 is available in 275 gallon totes (Net Wt. 2200 lbs), 55 gallon drums (Net Wt. 440 lbs) and 5 gallon pails (Net Wt. 40 lbs).

DOT Classification is Non Regulated.

Demonstration



Soiled Automotive Upholstery Leather

Cleaned with Diluted Flexiclean LC200

This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' patent rights.