



innovative chemical technologies, inc.

FLEXISTOP AF-333

TECHNICAL DATA SHEET

- ◆ **Very Efficient Water Soluble Non-Silicone Defoaming Agent**
- ◆ **Compatible With Nonionic, Cationic And Anionic Systems**
- ◆ **Effective Over A Wide pH Range (2 thru 12)**
- ◆ **Ideal For Use In Carpet Extraction Cleaners To Provide Rapid Defoaming With No Negative Resoiling**
- ◆ **Low Use Levels Required (0.1 – 2.0%)**
- ◆ **Environmentally Friendly: Low Oral And Aquatic Toxicity, And Readily Biodegradable**
- ◆ **Complies With FDA Regulations For Incidental Foodstuff Contact**

APPLICATIONS

- ◆ **Carpet Extraction Cleaners**
- ◆ **Aqueous Paints, Coatings, Hydraulic And Metal Working Fluids**

TYPICAL PROPERTIES

Appearance	Clear to Hazy, Pale Yellow Liquid
Density @ 20C	1.05 +/- 0.02
pH	7.5 +/- 0.5
Water Solubility	Soluble

PACKAGING/HANDLING

Flexistop AF-333 is available in 55 gallon drums (Net Wt. 441 lbs) and
5 gallon pails (Net Wt. 40 lbs).
DOT Classification is Non Regulated