

FlexisurfTM SS-40E Disodium Laureth Sulfosuccinate

Overview

- 40% solids Disodium Laureth Sulfosuccinate in water
- Mild anionic surfactant
- Excellent foaming properties, foam booster
- Sulfate free
- Biodegradable
- INCI Name: Disodium Laureth Sulfosuccinate
- CAS# 68815-56-5
- Ross Miles Foam Test Data: 5% Dilution

289 mm Initial Foam Height
243 mm after 3 min.
228 mm after 5 min.
204 mm after 10 min.
10% Dilution
364 mm Initial Foam Height
308 mm after 3 min.
299 mm after 5 min.

213 mm after 10 min.

Applications

- Hand Dishwash Liquid Detergent
- Cleaning formulations for carpet, upholstery, and textiles
- Component in personal care formulations such as shampoo, for mildness to skin and reduced eye irritation

Technical Information

Mild anionic surfactant which is biobased and provides excellent foaming properties. Nearly colorless liquid. The mild surfactant reduces eye irritation.

Uses include Hand Dishwash Liquid Detergent; component for cleaning formulations for carpet, upholstery, and textiles; and a component for personal care formulations such as shampoo with reduced eye irritation.

Naturally derived, Flexisurf SS-40E contains at least 55% biorenewable carbon.

Formulary

Recommended use levels of 0.5 to 10%. For diluted formulations, a preservative is recommended.

Typical Properties

PROPERTY	VALUE
Appearance	Clear liquid, colorless to pale yellow
Ionic character	Anionic
рН	6.0 - 7.0
Water solubility	Soluble
Solids, %	40.0±1.0
Viscosity	< 200 cps
Density@25°C	1.09 ±0.2 g/ml
Odor	Mild
Flash point	> 100°C
Storage	Not stable to freez- ing. Storage and handling below 40°C is recom- mended.
Shelf life	6 months

Packaging and Handling

Flexisurf SS-40E is available in: 275 gallon totes (Net Wt. 2250 lbs) 55 gallon plastic drums (Net Wt. 450 lbs) 5 gallon plastic pails (Net Wt. 40 lbs)

Refer to the Safety Data Sheet (SDS) for information on the safe use, handling, and disposal of this product.

DOT Classification: Non-Regulated

Whether you are looking for a replacement product or an ingredient for a specific attribute, give us a call. We can provide assistance based upon your particular formulation requirements and composition. Please feel free to contact us.

Flexisurf SS-40E Disodium Laureth Sulfosuccinate

This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' intellectual property rights. ID# 20180208



© Innovative Chemical Technologies, Inc. • 103 Walnut Grove Rd, Cartersville, GA 30120 • 770.607.9340 • www.ictchemicals.com