



Product Line

Nonfluorinated Paints & Coatings Additives

Product	Ionic Character	pH	Benefits	Applications	Solubility	Recommended Use Level
Flexiwet CZ-1000	Free acid, 580 mg. KOH/g	1 to 3	Excellent Anti-blocking	Paints & Coatings	Self-dispersible in water, with added IPA or glycol	0.1 to 1.0% (as sold) in formulation
			Leveling & Wetting			
			Adhesion promotion			
Flexiwet CZ-1040K	Pre-neutralized Slightly alkaline	5 to 8	Excellent Anti-blocking	Paints & Coatings	Water soluble	0.2 to 2.0% (as sold) in formulation
			Leveling & Wetting			
			Adhesion promotion			
Flexiwet CZ-1100	Free acid, 330 mg. KOH/g	1 to 3	Anti-blocking	Floor Care	Self-dispersible in water, soluble in IPA & ethanol	0.15 to 0.35% (as sold) in formulation
			Leveling & Wetting	Paints & Coatings		
			Compatibility with acrylic & wax emulsions	Multi-coat applications		
ICT-1566L	Free acid, 330 mg. KOH/g	1 to 3	Anti-blocking	Paints & Coatings	Self-dispersible in water, soluble in IPA & ethanol	0.15 to 0.35% (as sold) in formulation
			Shorter block times (4 hrs.)	Deep base paint		
			Leveling & Wetting			
			Performs in hot conditions			
ICT-1628L	Pre-neutralized Anionic	7 to 9	Anti-blocking	Paints & Coatings	Soluble/dispersible in water, soluble in IPA & ethanol	0.2 to 2.0% (as sold) in formulation
			Shorter block times (4 hrs.)	Deep base paint		
			Leveling & Wetting			
			Performs in hot conditions			



This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' intellectual property rights. ID# 20240624

