

# Flexiwet<sup>™</sup> CZ-1240K

Non-fluorinated Surfactant

#### **Overview**

- Non-fluorinated surfactant mixture
- Provides anti-blocking for paints & coatings
- · Surface tension reduction
- Powerful wetting and leveling performance for smoother, defectfree coatings & improved open time
- Does not impart color, or change • the optical properties of a coating (beyond potential gloss or DOI distinctness of image)

#### **Applications**

- Additive for paints & coating
- · Additive for adhesives
- · Additive for mold release
- Additive for polishes & lacquers
- Surfactant for HI&I cleaning

#### **Technical Information**

Flexiwet CZ-1240K is a non-fluorinated surfactant mixture for use in paints & coatings.

Surface tension reduction can be achieved at low loading levels. This product is an excellent choice for wetting difficult-to-wet substrates. The excellent wetting and leveling provides smoother, defect-free coatings. Surface diffusion properties of Flexiwet CZ-1240K deliver block resistance.

#### Formulary

This product is water soluble. The recommended use level for Flexiwet CZ-1240K is 0.2 to 2.0 wt. % (as sold) in the final formulation.

Flexiwet CZ-1240K can be incorporated during the letdown phase of production or post-added to the final formulation.

#### **Typical Properties\***

PROPERTY	VALUE
Appearance	Liquid
Color	Colorless
Odor	Mild
% Solids	38 to 42
Ionic character	Anionic
Water Solubility	Soluble
pH (as is)	5 to 8
Density@25°C	1.08 to 1.12 g/ml
Boiling Point	> 94°C
Flash point	> 94°C (closed cup)
Storage	Protect from freezing
Shelf life	12 months

\*Typical Properties do not represent specification ranges.

### **Packaging and Handling**

Flexiwet CZ-1240K is available in: 275 gallon totes (2375 lb. net wt.), 55 gallon drums (475 lb. net wt.), 5 gallon pail (40 lb. net wt.)

Refer to the Safety Data Sheet (SDS) for information on the safe use, handling, and disposal of this product.

DOT Classification: Not DOT regulated

Whether you're looking for a replacement product or an ingredient for a specific attribute, give us a call. We can provide assistance based upon your particular formulation requirements and composition; please feel free to contact us.

## Flexiwet CZ-1240K Non-fluorinated Surfactant

This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' intellectual property rights. ID# 20250313



© Innovative Chemical Technologies, Inc. • 103 Walnut Grove Rd, Cartersville, GA 30120 • 770.607.9340 • www.ictchemicals.com