



Flexisperse™ 350N

Antiscalant/Dispersant polymer

Overview

- Liquid, fully neutralized sodium polyacrylate in water
 - Designed as an excellent general purpose antiscalant, effective over a broad range of pH, water hardness and temperature conditions
 - Prevents formation of a wide variety of scales through multiple mechanisms including sequestration of hardness ions, crystal distortion or modification, and dispersion
 - Cost effective and thermally stable dispersant for high solids slurries of inorganic pigments
 - Excellent dispersant for calcium phosphate, calcium carbonate, iron oxide, and silicate with a single product
 - INCI name: Sodium Polyacrylate
 - FDA 21 CFR Food Additive approvals:
 - §173.310 Boiler water additive*
 - §175.105 Adhesives
 - §176.170 Components of paper
 - §176.180 Components of paper
- *when fully neutralized with sodium

Applications

- Oil Field scale inhibitor for preventing scale in well formation and production equipment
- Oil Field drilling deflocculant, particularly in fresh water drilling muds
- Industrial Water Treatment and Desalinization

Technical Information

Flexisperse 350N is a fully neutralized sodium polyacrylate homopolymer specifically designed for scale and hardness control.

In Oil Field applications, Flexisperse 350N helps to control scale development in well formations as well as production equipment. Flexisperse 350N is a functional dispersant/ deflocculation agent and flow modifier for drilling fluids, particularly fresh water drilling muds.

Also used for Industrial Water Treatment to control the formation of CaCO_3 , CaSO_4 and other mineral salt scales on heat exchange surfaces of cooling towers and boilers.

Flexisperse 350N is a cost effective and thermally stable dispersant for a variety of inorganic pigments including Kaolin Clay, CaCO_3 , TiO_2 , and Iron Oxides.

Formulary

Use at a rate of 5-10 ppm solids to control scale build-up in cooling towers, boilers and heat exchangers. In Oil Field applications, 5-10 ppm solids is effective for scale control on equipment and downhole.

Typical Properties

PROPERTY	VALUE
Appearance	Clear liquid
Color	Colorless to light yellow
Odor	Mild
Ionic character	Anionic
Water solubility	Miscible
Average molecular weight (Mw)	2500-3500
Viscosity @25°C (Brookfield), MPa-s/cps	50-100
Total solids, %	40.0±1.0
pH (as is)	4.0±1.0
Density@25°C, g/ml	1.20±0.1
Boiling Point	100°C
Flash point	Non-combustible
Storage	Stable to freezing
Shelf life	12 months

Packaging and Handling

Flexisperse 350N is available in:
275 gallon totes (Net Wt. 2750 lbs)
55 gallon plastic drums (Net Wt. 550 lbs)

Refer to the Safety Data Sheet (SDS) for information on the safe use, handling, and disposal of this product.

DOT Classification: Non-Regulated

Whether you're looking for a replacement product or an ingredient for a specific attribute, give us a call. We can provide assistance based upon your particular formulation requirements and composition; please feel free to contact us.

Please refer to back page for important information

Flexisperse 350N

Effective Scale Inhibition and Dispersion

With an optimal molecular weight and molecular weight distribution in the recognized effective range of 2,500-3,500, Flexisperse 350N treatment inhibits scale formation by three primary, non-stoichiometric mechanisms: **Threshold effect**, **Crystal Distortion effect**, and **Dispersion properties**.

Threshold Effect

Flexisperse 350N exhibits a Threshold/Solubility enhancement effect, associating and complexing with hard water ions to retard the formation of insoluble hard water salts or scale “seeds,” and preventing scale seeds from growing into scale crystals. Flexisperse 350N polymer strands adsorb onto formed seeds, and act to delay crystal nucleation and subsequent growth and resultant scale formation.

Crystal Distortion Effect

For formed and growing crystals, Flexisperse 350N polymer strands adsorbed onto the crystal matrix distort and disrupt the crystal growth. The Crystal Distortion effect results in irregular, readily fracturable particles that do not effectively adhere to surfaces and are more easily removed during cleaning processes.

Dispersion Properties

Flexisperse 350N adsorbed onto crystals and particles resists agglomeration through electrostatic repulsion, and/or steric hindrance and acts to disperse the crystals and particles. Dispersed crystals and particles are less likely to deposit on surfaces, and once in solution, less likely to redeposit. Through the mechanism of electrostatic repulsion, Flexisperse 350N works effectively as a dispersant of inorganic mineral pigments. An effective dispersant may significantly reduce the energy required to incorporate solids into a dispersion, reduce the viscosity of a dispersion or paste, and allow for higher solids loading in the dispersion.

Unlike sequestering agents that function necessarily on a stoichiometric basis, Flexisperse 350N functions at very low ratios of polymer to precipitating salt. For example, as little as 5 ppm Flexisperse 350N can avoid precipitation of as much as 500 ppm CaCO_3 . Unlike stoichiometric sequestering agents, the mixed mechanism of Threshold effect, Crystal Distortion effect, and Dispersion properties exhibited by Flexisperse 350N does not result in metal complexes that can react or catalyze reactions.

Applications

The unique calcium salt solubilization properties of Flexisperse 350N in Oil Field applications allow use as a scale inhibitor for preventing calcium salt scale downhole and on production equipment. Other Flexisperse 350N Oil Field applications include use in the formulation of aqueous drilling fluids as flow modifiers, stabilizers, sticking control additives and deflocculants. Flexisperse 350N is a functional dispersant/deflocculation agent and flow modifier for drilling fluids, particularly fresh water drilling muds.

In Industrial water treatment, especially open recirculating cooling towers and circuits, Flexisperse 350N is effective at inhibiting scale formation and precipitation of calcium carbonate, calcium oxalate, calcium sulfate, barium sulfate and other low solubility salts. Other Industrial water treatment applications include use as a dispersant for boiler sludge control.

Acute and chronic toxicity tests demonstrate that under US EPA criteria, polycarboxylates are “practically non-toxic,” the lowest EPA category for toxicity, to aquatic organisms. Flexisperse 350N is listed and in compliance with the major chemical registries in the world.

This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' intellectual property rights. ID# 20160610