



Product Line

Nonfluorinated Paints & Coatings Additives

Product	Ionic Character	pH	Benefits	Applications	Solubility	Recommended Use Level
Flexiwet CZ-1000	Anionic	1 to 3	Excellent Anti-blocking	Paints & Coatings	Self-dispersible in water,	0.1 to 1.0% (as sold)
			Leveling & Wetting		with added IPA or glycol	in formulation
			Adhesion promotion			
Flexiwet CZ-1040K	Pre-neutralized (Potassium salt)	5 to 8	Excellent Anti-blocking	Paints & Coatings	Water soluble	0.2 to 2.0% (as sold)
			Leveling & Wetting			in formulation
			Adhesion promotion			
Flexiwet CZ-1100	Anionic	1 to 3	Anti-blocking	Paints & Coatings	Self-dispersible in water,	0.15 to 0.35% (as sold)
			Leveling & Wetting	Floor Care	soluble in IPA & ethanol	in formulation
			Compatibility with acrylic	Multi-coat applications		
			& wax emulsions			
Flexiwet CZ-1200	Anionic	1 to 3	Excellent Anti-blocking	Paints & Coatings	Self-dispersible in water,	0.1 to 1.0% (as sold)
			Leveling & Wetting		with added IPA or glycol	in formulation
			Adhesion promotion			
Flexiwet CZ-1240K	Pre-neutralized (Potassium salt)	5 to 8	Excellent Anti-blocking	Paints & Coatings	Water soluble	0.2 to 2.0% (as sold)
			Leveling & Wetting			in formulation
			Adhesion promotion			



This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' intellectual property rights. ID# 20260526

